Go utility

Originally created to assist the NetYCE developers to jump between the various directories of the application when using the bash CLI, the **go** utility offers sufficient benefits for the application manager to warrant some explanation.

The go utility is loaded automatically when logging in as **yce** user but can also be sourced by any bash shell from /opt/yce/system/go

Jumping directories

To use the utility, simply use it as a command with one or two arguments: go <cmd>. There are several reserved commands that can be used to manipulate YCE flag files and processes, but anything else is taken as a partial directory name. If that name matches an existing directory within the YCE application, a cd to that locations is executed.

for example, the user jumps first to the 'netyce 'system' directory, then to the 'logs' directory, and finally back to his previous directory (being the system dir):

```
$ go sys
goto sys -> /opt/yce/system
yce@yceseven /opt/yce/system
$
$ go logs
goto logs -> /var/opt/yce/logs
yce@yceseven /var/opt/yce/logs
$
$ go -
goto /opt/yce/system
/opt/yce/system
yce@yceseven /opt/yce/system
$
```

The jumps are initially tried as case sensitive but failing a match are attempted as case INsensitive:

```
$ go YCE
goto YCE -> /opt/yce/YCE
yce@yceseven /opt/yce/YCE
$ go yce
goto yce -> /opt/yce/htdocs/angular/assets/js/yce
yce@yceseven /opt/yce/htdocs/angular/assets/js/yce
$ go nms
goto nms -> /var/opt/mysql/NMS
yce@yceseven /var/opt/mysql/NMS
$
```

```
Last update: 2024/07/03 maintenance:general:tools:go_utility https://wiki.netyce.com/doku.php?id=maintenance:general:tools:go_utility
```

To optimize performance, the available directories are loaded on the first use of the go jump facility. To allow jumping to the more dynamically created job directories using the job ID, the available directories are reloaded when the typed name is longer than 8 characters.

The example below demonstrates the initial jump, a subsequent jump and a jump to a job ID:

```
$ go etc
loading paths...
goto etc -> /opt/yce/etc
yce@yceseven /opt/yce/etc
$ go logs
goto logs -> /var/opt/yce/logs
yce@yceseven /var/opt/yce/logs
$ go 0915_0053
loading paths...
goto 0915_0053 -> /var/opt/yce/jobs/0915_0053
yce@yceseven /var/opt/yce/jobs/0915_0053
$
```

Special jumps

As illustrated in the go - of the first example, there are some jumps with special meaning.

- The location will jump to the previous jump or cd you used.
- The . location will jump to /opt/yce.
- The **xjob** will jump you to the most recent (highest) job ID directory.

Application processes

"Go" also has some process reporting and manipulation facilities that are specific to the YCE application.

go ps

The Unix standard 'ps' command is very versatile and powerful, but is hard to use and requires indepth knowledge of all the application's processes to find out what is running properly or what processes are missing.

The **go ps** command creates a very NetYCE specific overview of the various daemons and processes, but also reports on processes that are missing and flag status. The output is similar to 'ps':

×

It shows all processes running under the yce user or are part of the NetYCE application. The column FNAME has the name of the process which will often be different from the command name. Indentation of the FNAME also indicates the parent - child relationships.

NetYCE daemon processes have their FNAME printed in blue.

3/7

At the bottom of the list, any missing processes are listed in red. Any process-ignore flags-files found are also listed here. The example above demonstrates that the yce_nccmd daemons is missing and that the process will not be restarted by the yce_psmon (process monitor daemon) because the flag file for the nccmd process exists.

go down

The **go down** command shuts the entire NetYCE application down. All daemons are killed and when done, the **go ps** results are displayed.

<pre>\$ go down halting Net stop 'psmor Stopping da stop 'mojo Stopping da stop 'morbo Daemon 'mor stop 'httpo Stopping ht stop 'yce_' stop 'vsft</pre>	tYCE aemon 'y aemon 'r o' rbo' nof d' ttpd: * daemor od'	yce_psmon' nojo' t running ns'					[ОК]	
Shutting down vsftpd:								0K	1	
stop 'mysql'										
Shutting down MySQL. SUCCESS!										
UID	PID	PPID	%MEM	%CPU	START	FNAME				CMD
усе	6833	6831	0.09	0.02	08:07:10	sshd				sshd:
yce@pts/1										
усе	6834	6833	0.12	0.02	08:07:10	bash				-bash
	yce_psmon mysqld_safe mysqld		not running not running not running							
	httpd		not running							
	vsftpd		not running							
	yce_tftpd yce_sched		not running							
			not running							
	mojo		not running							
	yce_xch		not running							
yce_nccmd			not running							
	yce_nc	cmd	ignore	flag	'/opt/yce/e	tc/ignore	e_n	ccmd	' is	set
	yce sku	ulker	not ru	nning						

go up

The **go up** command is used to launch the entire applications after the 'down' was issued. It removes all process ignore flags beforehand.

restart

The **go restart** <proc> is used to stop and immediately restart the NetYCE daemon process indicated with '<proc>'.

The valid values for '<proc>' are:

- 'mysql' (will use sudo)
- '**httpd**' or 'yce_httpd' (will use sudo)
- '**psmon**' or 'yce_psmon' (will use sudo)
- '**vsftpd**' (if installed; will use sudo)
- 'skulker' or 'yce skulker'
- '**xch**' or 'yce xch'
- '**nccmd**' or 'yce_nccmd'
- 'sched' or 'yce_sched'
- 'tftp' or 'yce tftp'
- 'ibd' or 'yce_ibd' (if the Infoblox integration is licensed)

The go restart command may be abbreviated to go res.

NOTE: some restart commands will under the current implementation not function properly. This limitation will be resolved in version 7.1.

Application flags

NetYCE uses within its application two types of application-flags that control process behaviour. These are the **debug flags** and the **ignore flags**.

Both types use the 'go' commands **go set** <flag> and **go clear** <flag>. The 'set' creates the flag file, the 'clear' removes it. The 'clear' command may also be invoked as **go clr** <flag>.

Debug flags

The two debug flags are:

• debug

This flag file controls the debug logging of *all* NetYCE daemons. The daemons will detect the debug mode at startup (requiring restart), although some will do this dynamically. The debug flag file corresponds with /opt/yce/etc/yce_debug. When present, the debug mode is enabled.

• dev

This flag controls the (very) extensive (development) logging of the vendor modules that are used to communicate with the network devices. It should not be activated on servers unless requested by NetYCE support.

The debug flag file corresponds with /opt/yce/etc/yce_development. When present, the debug mode is enabled.

The go set dev and go clear dev command affects *both* the debug and the development flags.

When the **debug** flag is set, the following files are used:

- yce_auth_debug.log
- yce_db_debug.log
- yce_morbo_debug.log
- yce_nccm_debug.log
- yce_st_debug.log
- yce_cgi_debug.log
- yce_skulker_debug.log
- yce_tftp_debug.log

When the **development** flag is set, the following file is used:

• yce_dev_debug.log

All the log files are located in /var/opt/yce/logs.

Ignore flags

The **ignore** flags control the NetYCE process monitoring for the various daemons. The monitoring is performed by the **yce_psmon** daemon which should be running at all times to ensure proper application behaviour.

Monitoring by yce_psmon ensures that the process is behaving within some constraints for cpu usage and number of child processes. When ill-behaved the process is killed and re-spawned. Should a process die by itself or be killed by a user, the process is likewise re-spawned. The parameters for each process it must monitor are specified in the configuration file

/opt/yce/etc/<servername>_psmon.conf. This file is automatically created when installing a
version (update).

The yce_psmon has a unique flag file configured for each of its daemons. When the flag file is present it indicates the yce_psmon should NOT monitor this process. To stress this behaviour, the flag file is named after the process name prepended by "ignore_".

The ignore flags can be controlled using the **go set** <flag> and **go clear** <flag> commands. The values for <flag> and their corresponding files are:

- 'mysql' sets /opt/yce/etc/ignore_mysql
- 'httpd' sets /opt/yce/etc/ignore_httpd
- '**skulker**' sets /opt/yce/etc/ignore_skulker
- '**xch**' sets /opt/yce/etc/ignore_xch
- 'mojo' sets /opt/yce/etc/ignore_mojo
- 'sched' sets /opt/yce/etc/ignore sched
- 'nccmd' sets /opt/yce/etc/ignore_nccmd
- 'tftpd' sets /opt/yce/etc/ignore_tftpd
- 'ibd' sets /opt/yce/etc/ignore_ibd

Log file shortcuts

NetYCE support and developers frequently examine (debug) log files. Some specific log-file access shortcuts were included in the 'go' utility to simplify these tasks.

These shortcuts are only useful if the **debug** and/or **development** flags are set.

Database logging

• go db

Opens 'less' on the yce database debug file /var/opt/yce/yce_db_debug.log. Use 'q' to exit, 'G' to goto last entry, '/<pat>' to search forward, '?<pat>' to search backwards.

• go tdb

Opens 'tail -f' on the yce database debug file.

• go cdb

Clears the yce database debug file by cp /dev/null /var/opt/yce/yce_db_debug.log.

Development logging

• go dev

Opens 'less' on the yce development debug file /var/opt/yce/yce_dev_debug.log. Use 'q' to exit, 'G' to goto last entry, '/<pat>' to search forward, '?<pat>' to search backwards.

• go tdev

Opens 'tail -f' on the yce development debug file. Use '<control>-C' to exit.

• go cdev

Clears the yce development debug file by cp /dev/null /var/opt/yce/yce_dev_debug.log.

Development compare

A special command was included to compare two files side by side *on different servers*. This is used mostly to find code changes between different versions.

The command uses vimdiff to show the files side by side. Refer to Vim manuals to learn how to operate 'vi' or 'vim' in this mode.

The **go cmp** <file> can only be invoked when <file> resides in the current directory and is present on the local server AND the server against which to compare.

This remote server must be defined in the environment parameter RDEV. It is set in /home/yce/.bash_profile:

```
if [ -r "/opt/yce/system/go" ]; then
    export RDEV="ycesix"
```

```
source "/opt/yce/system/go"
else
echo "Skipping 'go'"
fi
```

From: https://wiki.netyce.com/ - **Technical documentation**

Permanent link: https://wiki.netyce.com/doku.php?id=maintenance:general:tools:go_utility



Last update: 2024/07/03 12:31